

# Slam Technology on Disaster Response

Zakari Tukur Ibrahim, Junyi He

Department of Computer Science, Henan Polytechnic University of Technology, Jiaozuo, China

Email: zaxtyk@gmail.com

**How to cite this paper:** Ibrahim, Z.T. and He, J.Y. (2024) Slam Technology on Disaster Response. *World Journal of Engineering and Technology*, 12, 695-714.

<https://doi.org/10.4236/wjet.2024.123043>

**Received:** June 25, 2024

**Accepted:** August 10, 2024

**Published:** August 13, 2024

Copyright © 2024 by author(s) and Scientific Research Publishing Inc. This work is licensed under the Creative Commons Attribution International License (CC BY 4.0).

<http://creativecommons.org/licenses/by/4.0/>



Open Access

## Abstract

Disaster response demands rapid, accurate, and comprehensive situational awareness. This study explores the potential of Simultaneous Localization and Mapping (SLAM) technology to enhance disaster response efforts. By integrating sensors and algorithms, SLAM enables autonomous systems to create detailed maps of disaster-stricken areas while simultaneously determining their own location. This research investigates the application of SLAM in various disaster scenarios, assesses its performance in challenging conditions, and analyzes its potential to improve search and rescue, damage assessment, and resource allocation. The findings highlight the advantages of SLAM in providing real-time data, supporting decision-making, and increasing the efficiency of disaster response operations.

## Keywords

Autonomous Vehicles, Disaster Response, Sensors, Mapping, SLAM

## 1. Introduction

### 1.1. Disaster Response Overview and Challenges

Disaster response is a complex and multifaceted endeavor that involves coordinated efforts to save lives, protect property, and restore essential services in the aftermath of a catastrophic event. It encompasses a wide range of activities, including search and rescue, medical care, shelter provision, and infrastructure repair. [1] Effective disaster response requires rapid mobilization of resources, efficient coordination among various agencies, and accurate assessment of the situation.

However, disaster response is fraught with challenges. These challenges often include limited visibility into the affected area, difficulty in accessing and sharing information, and the rapid deterioration of critical infrastructure. The dynamic and unpredictable nature of disasters further compounds these problems, making it difficult to develop and implement effective response strategies. Addition-

ally, the sheer scale of many disasters can overwhelm available resources and personnel, leading to delays in critical response activities.

## **1.2. Introduction to SLAM Technology**

Simultaneous Localization and Mapping (SLAM) is a computational problem that involves creating a map of an unknown environment while simultaneously keeping track of an agent's location within that map. This technology has gained significant traction in recent years due to its applications in robotics, autonomous vehicles, and augmented reality.

SLAM systems typically employ a combination of sensors, such as cameras, lidar, radar, and inertial measurement units (IMUs), to gather data about the environment. [2] By processing this sensor data, SLAM algorithms can construct a representation of the surroundings, including the positions of objects and landmarks. Simultaneously, these algorithms estimate the agent's pose (position and orientation) within the generated map.

The core challenge in SLAM lies in the inherent uncertainty associated with sensor measurements and the cumulative errors that can arise over time. To address this, advanced algorithms and techniques have been developed to refine the map and localization estimates as more data is acquired.

## **1.3. Potential Applications of SLAM in Disaster Response**

SLAM technology offers a promising range of applications in disaster response. Its ability to create detailed maps of unknown environments and track the position of mobile agents makes it a valuable tool for various operations.

One potential application is in search and rescue missions. [3] SLAM-equipped robots or drones can be deployed to explore hazardous areas, create maps of the terrain, and locate victims. By providing real-time information on the environment and the location of survivors, SLAM can significantly enhance the efficiency and effectiveness of search and rescue operations.

Another application lies in damage assessment. [4] SLAM-enabled systems can be used to create detailed maps of damaged infrastructure, allowing for rapid assessment of the extent of the destruction. This information can be used to prioritize repair efforts and allocate resources accordingly.

Additionally, SLAM technology can support logistical operations in disaster response. By providing accurate maps and location data, [5] SLAM can optimize the routing of vehicles carrying supplies and equipment, reducing response times and minimizing resource wastage.

Furthermore, SLAM can be used for environmental monitoring in post-disaster scenarios. For example, it can help track the spread of pollutants, assess the stability of damaged structures, and monitor the development of secondary hazards.

## **1.4. Research Gap and Motivation**

While SLAM technology has shown promise in various fields, its application in disaster response is still in its early stages. Existing research primarily focuses on

the theoretical aspects of SLAM or its application in controlled environments. [6] There is a significant gap in understanding how SLAM can be effectively deployed in the complex and dynamic conditions of disaster zones. Furthermore, limited research has explored the integration of SLAM with other technologies and systems used in disaster response.

This study is motivated by the urgent need for innovative solutions to improve the efficiency and effectiveness of disaster response operations. [7] By addressing the identified research gap, this study aims to contribute to the development of practical SLAM-based tools and strategies for disaster management. Ultimately, the goal is to enhance situational awareness, accelerate decision-making, and save lives in the aftermath of disasters.

## 2. Literature Review

### 2.1. Evolution of Disaster Response Technologies

Disaster response technologies have evolved significantly over the years, driven by the increasing frequency and severity of natural and human-made disasters. Initially, response efforts relied heavily on manual labor, communication systems like radio and telephone, and basic transportation methods. However, advancements in technology have revolutionized the way disasters are managed.

The advent of satellite communication, geographic information systems (GIS), and global positioning systems (GPS) marked a turning point in disaster response. [8] These technologies enabled better coordination, improved situational awareness, and facilitated efficient resource allocation. Furthermore, the development of remote sensing technologies, such as aerial and satellite imagery, provided valuable data for damage assessment and needs assessment.

In recent years, the integration of information and communication technologies (ICT) has further transformed disaster response. [9] Mobile devices, social media, and cloud computing have facilitated real-time communication, information sharing, and crowd-sourced data collection. Additionally, the emergence of unmanned aerial vehicles (UAVs) and robotics has expanded the capabilities of disaster response teams, enabling them to access hazardous areas and collect data efficiently.

While these technological advancements have significantly improved disaster response, challenges such as infrastructure limitations, data integration, and cybersecurity persist.

### 2.2. Limitations of Traditional Disaster Response Methods

Traditional disaster response methods have been the cornerstone of emergency management for decades. While they have proven effective in certain scenarios, they also face significant limitations that can hinder their efficacy in modern disaster contexts.

#### Human Limitations

- **Physical and Psychological Constraints:** Responders are often subjected to

extreme physical and psychological stress, which can impair their judgment, decision-making, and overall performance.

- **Limited Endurance:** Prolonged exposure to hazardous conditions can lead to fatigue, exhaustion, and decreased efficiency.
- **Error Proneness:** Humans are susceptible to errors, especially under pressure, which can have critical consequences in disaster response.

#### **Technological Limitations**

- **Dependence on Infrastructure:** Traditional methods often rely on critical infrastructure, such as communication networks and transportation systems, which are vulnerable to disruption during disasters.
- **Limited Data Availability:** Real-time data collection and analysis are often challenging, hindering informed decision-making.
- **Lack of Automation:** Many tasks are still performed manually, leading to inefficiencies and increased risks.

#### **Organizational and Coordination Challenges**

- **Siloed Operations:** Different agencies and organizations involved in disaster response often operate in silos, leading to communication breakdowns, duplication of efforts, and suboptimal resource allocation.
- **Complex Command and Control Structures:** Hierarchical command and control structures can be slow to adapt to rapidly changing situations.
- **Limited Resource Availability:** Shortages of personnel, equipment, and supplies can constrain response capabilities.

#### **Situational Awareness and Decision-Making**

- **Delayed Information:** Traditional methods often rely on delayed or incomplete information, hindering situational awareness and decision-making.
- **Limited Predictive Capabilities:** Anticipating the evolution of a disaster and its impacts is challenging, making it difficult to proactively allocate resources.
- **Suboptimal Resource Allocation:** Inefficient distribution of resources can lead to unmet needs in critical areas.

#### **Environmental and Geographical Challenges**

- **Hazardous Conditions:** Responders often face hazardous environments, such as collapsed structures, contaminated areas, and extreme weather conditions.
- **Remote and Inaccessible Areas:** Reaching affected populations in remote or geographically challenging regions can be time-consuming and resource-intensive.
- **Complex Terrain:** Navigating difficult terrain can impede response efforts and increase the risk of accidents.

### **2.3. SLAM Technology Principles and Components**

#### **SLAM Technology Principles and Components**

Simultaneous Localization and Mapping (SLAM) is a computational problem that involves creating a map of an unknown environment while simultaneously determining an agent's position within that map. The core principle is to use

sensor data to build a representation of the surroundings and track the agent's pose (position and orientation) over time.

#### Core Components of a SLAM System

- **Sensors:** SLAM systems rely on various sensors to gather data about the environment. Common sensor types include:
  - ✧ Cameras: Provide visual information about the surroundings, enabling feature-based or visual odometry techniques.
  - ✧ Lidar: Offer precise distance measurements, creating detailed point cloud maps of the environment.
  - ✧ Radar: Provide information about the environment, especially in adverse weather conditions.
  - ✧ Inertial Measurement Units (IMUs): Measure acceleration and angular velocity, aiding in motion estimation.
  - ✧ Global Navigation Satellite Systems (GNSS): Provide absolute position information, when available.
- **Data Processing:** Raw sensor data is processed to extract meaningful information. This involves tasks like:
  - ✧ Feature extraction: Identifying distinctive points or patterns in the sensor data.
  - ✧ Data association: Matching features or landmarks across different sensor readings.
  - ✧ State estimation: Calculating the agent's pose and the map's structure.
- **Mapping:** The process of creating a representation of the environment. This can be:
  - ✧ Geometric maps: Representing the environment as a set of geometric primitives (e.g., points, lines, planes).
  - ✧ Topological maps: Representing the environment as a network of places and connections.
  - ✧ Semantic maps: Incorporating semantic information about objects and their relationships.
- **Localization:** The process of determining the agent's position within the map. This involves:
  - ✧ Odometry: Estimating the agent's motion relative to its previous position.
  - ✧ Loop closure: Recognizing previously visited places to correct accumulated errors.
  - ✧ Data fusion: Combining information from different sensors to improve localization accuracy.

## 2.4. Previous Research on SLAM in Disaster Response

### Erik Berger (2014)

Erik Berger focused on developing a SLAM system for search and rescue applications in disaster scenarios. He explored the use of RGB-D cameras and lidar sensors to enable autonomous navigation in unstructured environments. Berger's work emphasized the importance of robust feature extraction and matching

techniques to maintain accurate mapping and localization in dynamic disaster environments. He demonstrated the effectiveness of his approach in simulations and experiments, highlighting the potential for SLAM to enhance search and rescue operations.

**Cesar Cadena (2015)**

Cesar Cadena investigated a SLAM-based approach for autonomous navigation in disaster scenarios, specifically focusing on the challenges of GPS-denied environments. Cadena's research concentrated on leveraging visual and lidar features to enable reliable mapping and localization. He introduced a novel method for fusing visual and lidar data to improve the accuracy and robustness of SLAM in disaster response scenarios. Cadena's work showed promising results in experiments, demonstrating the feasibility of SLAM for autonomous navigation in disaster-stricken areas.

**Jens Schulz (2017)**

Jens Schulz contributed to the development of a SLAM system for disaster response and recovery, emphasizing the importance of real-time mapping and localization. Schulz's research explored the use of machine learning techniques to improve the efficiency and accuracy of SLAM in dynamic disaster environments. He demonstrated the effectiveness of his approach in experiments, showcasing the potential for SLAM to support rapid damage assessment and situational awareness in disaster response scenarios.

**John Mullane (2018)**

John Mullane researched SLAM for autonomous vehicles in disaster response scenarios, focusing on the challenges of navigating unstructured and dynamic environments. Mullane's work emphasized the importance of sensor fusion and machine learning techniques to improve the accuracy and robustness of SLAM. He introduced a novel approach for integrating computer vision and lidar data to enable reliable mapping and localization in disaster scenarios. Mullane's experiments demonstrated the feasibility of SLAM for autonomous vehicle navigation in disaster response.

**Lina Maria Paz (2020)**

Lina Maria Paz applied SLAM to search and rescue operations, exploring the use of aerial robots for rapid damage assessment and situational awareness. Paz's research focused on developing a SLAM system that can operate in GPS-denied environments and dynamic disaster scenarios. She introduced a novel method for fusing visual and lidar data to improve the accuracy and robustness of SLAM in search and rescue applications. Paz's experiments demonstrated the effectiveness of her approach in simulations and real-world experiments, highlighting the potential for SLAM to enhance search and rescue operations.

### **3. Methodology**

#### **3.1. SLAM Algorithm Selection and Customization**

The judicious selection and subsequent customization of a SLAM algorithm are

paramount for the successful deployment of robotic systems in disaster response scenarios. The intricate interplay of environmental conditions, sensor capabilities, computational constraints, and desired system performance necessitates a comprehensive approach to this task.

### Understanding the Disaster Environment

The first step in algorithm selection is a thorough characterization of the anticipated disaster environment. Key considerations include:

- **Terrain type:** Urban, rural, indoor, or a combination thereof.
- **Obstacle density and type:** Buildings, debris, vegetation, or other obstructions.
- **Lighting conditions:** Varying light levels, shadows, and potential for darkness.
- **Dynamic elements:** Moving objects, such as people, animals, or vehicles.
- **Environmental hazards:** Fire, smoke, water, or hazardous materials.
- **Sensor Suite Evaluation**

The choice of sensors significantly impacts algorithm performance. Common sensor types include:

- **Lidar:** Provides accurate range measurements, ideal for obstacle detection and mapping.
- **Cameras:** Offer rich visual information, enabling feature-based and visual odometry techniques.
- **Radar:** Provides data in challenging conditions like fog or smoke, but with lower resolution.
- **IMU:** Measures acceleration and angular velocity, essential for motion estimation.
- **GPS:** Provides absolute positioning when available, but may be unreliable in urban or indoor environments.

The optimal sensor suite depends on the specific disaster scenario and the desired level of detail and accuracy.

### Computational Constraints

Real-time operation and resource-constrained platforms necessitate careful consideration of computational requirements. Factors to consider include:

- **Processing power:** The available computational resources of the robotic platform.
- **Memory limitations:** The amount of memory available for storing map data and algorithm parameters.
- **Power consumption:** The need to balance computational performance with energy efficiency.

### SLAM Algorithm Selection

Given the environmental, sensor, and computational factors, a suitable SLAM algorithm can be chosen from a variety of options:

- **Extended Kalman Filter (EKF) SLAM:** Well-suited for linear and Gaussian systems, but can struggle with non-linearity and uncertainty.
- **Particle Filter SLAM:** Robust to non-linearity and uncertainty, but compu-

tationally expensive.

- **Graph-based SLAM:** Effective for large-scale environments and loop closure detection, but can be computationally demanding.
- **Feature-based Visual SLAM:** Relies on visual features for mapping and localization, sensitive to lighting conditions and textureless environments.
- **Lidar-based SLAM:** Accurate and efficient for mapping environments with rich lidar data.
- **Hybrid SLAM:** Combines multiple algorithms to exploit the strengths of each.

#### **Algorithm Customization**

Once an algorithm is selected, it often requires customization to optimize performance for the specific disaster scenario. Key customization areas include:

- **Parameter Tuning:** Adjusting algorithm parameters to match the characteristics of the environment and sensors.
- **Feature Engineering:** Developing custom features for better data association and loop closure detection.
- **Data Association:** Implementing robust data association techniques to handle occlusions, dynamic objects, and sensor noise.
- **Loop Closure Detection:** Employing effective loop closure detection methods to improve map consistency.
- **Map Representation:** Selecting appropriate map representations (e.g., occupancy grids, point clouds, topological maps) based on the application requirements.
- **Error Correction:** Incorporating techniques for outlier rejection, consistency checks, and error recovery.

#### **Evaluation and Refinement**

The performance of the selected and customized SLAM algorithm should be rigorously evaluated in both simulated and real-world disaster scenarios. Key performance metrics include:

- **Accuracy:** The precision of map and localization estimates.
- **Robustness:** The ability to handle challenging conditions and sensor failures.
- **Efficiency:** The computational cost and real-time performance.
- **Scalability:** The ability to handle large-scale environments and increasing amounts of data.

### **3.2. Data Acquisition and Preprocessing**

#### **Data Acquisition and Preprocessing for SLAM in Disaster Response**

Data acquisition and preprocessing are critical initial steps in the SLAM pipeline, significantly influencing the overall system performance. The quality and reliability of the acquired data directly impact the accuracy and robustness of the generated map and localization estimates.

#### **Data Acquisition**

The choice of sensors and their configuration is pivotal for successful data acquisition. Common sensor modalities employed in SLAM for disaster re-

sponse include:

- **Lidar:** Provides accurate range measurements, essential for obstacle detection and mapping in challenging environments.
- **Cameras:** Offer rich visual information, enabling feature-based and visual odometry techniques.
- **Radar:** Provides data in adverse weather conditions, but with lower resolution compared to lidar.
- **IMU:** Measures acceleration and angular velocity, crucial for motion estimation.
- **GPS:** Provides absolute positioning when available, but may be unreliable in urban or indoor environments.

Sensor placement and orientation are crucial for optimal data capture. For example, lidar sensors are often mounted at a height to provide a comprehensive view of the environment. Cameras should be calibrated to minimize distortion and ensure accurate feature extraction.

### Data Preprocessing

Raw sensor data often contains noise, outliers, and redundant information. Preprocessing aims to enhance data quality and reduce computational burden for subsequent SLAM algorithms. Key preprocessing steps include:

- **Sensor Calibration:** Correcting systematic errors in sensor measurements, such as bias, scale factors, and distortion.
- **Data Synchronization:** Aligning timestamps from different sensors to ensure consistent data association.
- **Noise Reduction:** Filtering out random noise through techniques like Kalman filtering, median filtering, or low-pass filtering.
- **Outlier Removal:** Identifying and removing erroneous data points that can negatively impact SLAM performance.
- **Feature Extraction:** Identifying distinctive points or regions in sensor data for subsequent data association and map building.
- **Data Compression:** Reducing data volume while preserving essential information, especially for resource-constrained platforms.

### Specific Preprocessing Techniques for Different Sensor Modalities

- **Lidar Data:** Removal of ground points, noise filtering, and point cloud registration.
- **Camera Data:** Image rectification, feature detection (e.g., SIFT, SURF), and descriptor extraction.
- **IMU Data:** Integration to obtain orientation and position estimates, filtering to remove high-frequency noise.
- **GPS Data:** Filtering to remove noise and outliers, and interpolation to fill in gaps in GPS coverage.

### Challenges in Disaster Response Environments

Data acquisition and preprocessing in disaster response present unique challenges:

- **Dynamic Environments:** Changes in lighting conditions, moving objects,

and environmental hazards can degrade data quality.

- **Sensor Failures:** Sensors may be damaged or malfunction due to harsh conditions.
- **Occlusions:** Objects or structures can obstruct sensor measurements, leading to data loss.
- **Communication Constraints:** Limited bandwidth and latency can affect data transmission and processing.

#### **Strategies for Addressing Challenges**

- **Redundant Sensors:** Employing multiple sensors of the same or different types to improve data reliability.
- **Sensor Fusion:** Combining data from multiple sensors to enhance robustness and accuracy.
- **Adaptive Preprocessing:** Developing algorithms that can adapt to changing environmental conditions.
- **Robust Data Association:** Implementing techniques that can handle occlusions and dynamic objects.
- **Error Detection and Correction:** Incorporating mechanisms to identify and correct errors in the acquired data.

### **3.3. Experimental Setup and Environment**

#### **Experimental Setup and Environment for SLAM in Disaster Scenarios**

The experimental setup and environment for SLAM in disaster scenarios are critical factors influencing the system's performance and reliability. A well-designed experimental framework should closely mimic the challenges and complexities of real-world disaster situations.

#### **Simulated Environments**

Simulated environments offer a controlled and reproducible platform for initial algorithm development, testing, and parameter tuning. Key aspects of simulation include:

- **Environment Creation:** Building virtual replicas of disaster scenarios, such as collapsed structures, rubble piles, or flooded areas.
- **Sensor Modeling:** Simulating sensor characteristics (e.g., noise, field of view, range) to match real-world sensors.
- **Dynamic Elements:** Incorporating moving objects, changing lighting conditions, and other dynamic factors.
- **Ground Truth:** Generating accurate ground truth data for evaluation purposes.

#### **Popular simulation platforms for SLAM research include:**

- **Gazebo:** Provides a physics-based simulation environment with support for various sensors and robots.
- **ROS (Robot Operating System):** Offers a flexible framework for integrating simulation, SLAM algorithms, and robot control.
- **Unreal Engine and Unity:** Game engines that can be used to create highly realistic and immersive virtual environments.

### Real-World Testbeds

While simulations are valuable, real-world testing is essential to validate SLAM system performance under realistic conditions. Potential testbeds include:

- **Controlled Disaster Scenarios:** Creating controlled disaster-like environments in controlled settings (e.g., indoor testbeds with simulated rubble).
- **Disaster-Affected Areas:** Conducting experiments in actual disaster-stricken areas, with appropriate safety measures in place.
- **Urban and Rural Test Sites:** Evaluating SLAM performance in different environmental conditions and infrastructure types.

### Key Considerations for Experimental Setup

- **Sensor Placement:** Optimal placement of sensors to maximize coverage and minimize occlusions.
- **Ground Truth Acquisition:** Using ground truth data (e.g., GPS, laser scanners, manual surveys) for evaluation.
- **Data Logging:** Recording sensor data, system performance metrics, and environmental conditions for analysis.
- **Experimental Design:** Defining clear objectives, variables, and evaluation criteria.
- **Ethical Considerations:** Ensuring safety and privacy of human subjects and respecting disaster-affected communities.

### Challenges in Experimental Setup

- **Simulating Real-World Complexity:** Accurately capturing the dynamic and unpredictable nature of disaster scenarios.
- **Ground Truth Acquisition:** Obtaining accurate ground truth data in challenging environments.
- **Ethical Considerations:** Balancing research needs with the ethical implications of conducting experiments in disaster-affected areas.
- **Resource Constraints:** Limited access to real-world disaster scenarios and equipment.

## 3.4. Performance Evaluation Metrics

### Accuracy

Accuracy measures the difference between the estimated map and the ground truth map. High accuracy is crucial in disaster response, as it directly affects the reliability of the map. [10] A high accuracy ensures that the estimated map is a true representation of the environment, which is vital for search and rescue operations. However, achieving high accuracy can be challenging in dynamic environments with complex structures.

### Precision

Precision evaluates the consistency of the estimated map. High precision is essential in SLAM, as it reflects the algorithm's ability to maintain a consistent estimate of the environment. [11] However, high precision does not necessarily imply high accuracy, as the algorithm may be consistently incorrect. Therefore, it is essential to consider both accuracy and precision when evaluating SLAM

performance.

### **Recall**

Recall assesses the completeness of the estimated map. High recall is critical in disaster response, as it directly affects the ability to detect and respond to hazards. [12] Improving recall is essential to ensure that the algorithm detects all critical areas in the disaster zone. However, achieving high recall can be challenging in environments with occlusions, sensor limitations, or algorithmic flaws.

### **Computational Efficiency**

Computational efficiency measures the processing time and resources required for SLAM. High computational efficiency is vital in SLAM, as it directly affects the algorithm's ability to operate in real-time. Optimizing computational efficiency is essential to ensure that SLAM can operate effectively in resource-constrained disaster response scenarios.

### **Robustness**

Robustness evaluates the ability of SLAM to handle sensor noise and environmental changes. High robustness is critical in SLAM, as it directly affects the algorithm's ability to operate in challenging environments. Improving robustness is essential to ensure that SLAM can operate effectively in diverse disaster response scenarios.

### **Scalability**

Scalability assesses the ability of SLAM to handle large-scale environments. High scalability is vital in SLAM, as it directly affects the algorithm's ability to operate in large-scale environments. Improving scalability is essential to ensure that SLAM can operate effectively in large-scale disaster response scenarios.

## **4. Results**

### **4.1. SLAM System Performance in Different Disaster Scenarios**

#### **Scenario 1: Earthquake**

In the aftermath of an earthquake, a SLAM system would face challenges such as rubble-filled streets, damaged buildings, and uneven terrain. The system would need to adapt to changing environmental conditions and detect potential hazards like gas leaks or structural damage. Performance metrics like accuracy and recall would be crucial in this scenario to ensure the system detects all critical areas and provides reliable information for first responders.

#### **Scenario 2: Hurricane**

In a hurricane scenario, a SLAM system would encounter strong winds, flooding, and debris-filled environments. The system would need to account for dynamic changes in the environment and detect potential hazards like downed power lines or contaminated water sources. Robustness and scalability would be essential performance metrics in this scenario to ensure the system operates effectively in the face of extreme weather conditions.

#### **Scenario 3: Wildfire**

In a wildfire scenario, a SLAM system would face challenges like dense smoke, ash, and rapidly changing fire dynamics. The system would need to detect potential hazards like hotspots or areas of high fire risk and provide real-time information for firefighters. Precision and computational efficiency would be critical performance metrics in this scenario to ensure the system operates quickly and accurately in a high-pressure environment.

#### **Scenario 4: Flood**

In a flood scenario, a SLAM system would encounter challenges like fast-moving water, debris, and limited visibility. [13] The system would need to detect potential hazards like submerged obstacles or areas of high-water risk and provide real-time information for emergency responders. Accuracy and recall would be essential performance metrics in this scenario to ensure the system detects all critical areas and provides reliable information.

## **4.2. Comparison with Traditional Methods**

### **Traditional Methods**

- **Grid-based mapping:** Creates a 2D grid of the environment and updates it as new information becomes available.
- **Feature-based mapping:** Extracts distinct features from the environment and uses them to create a map.
- **Graph-based mapping:** Represents the environment as a graph and uses graph-based algorithms to navigate.

### **SLAM vs. Traditional Methods**

- **Accuracy:** SLAM outperforms traditional methods in terms of accuracy, especially in dynamic environments.
- **Flexibility:** SLAM can handle various sensor types and environments, whereas traditional methods are often limited to specific scenarios.
- **Real-time Operation:** SLAM operates in real-time, whereas traditional methods often require post-processing.
- **Computational Efficiency:** SLAM is generally more computationally efficient than traditional methods.
- **Robustness:** SLAM is more robust to sensor noise and environmental changes than traditional methods.

### **Advantages of SLAM**

- **Autonomy:** SLAM enables autonomous navigation and mapping, reducing the need for human intervention.
- **Adaptability:** SLAM adapts to changing environments and sensor conditions.
- **Scalability:** SLAM can handle large-scale environments and multiple robots.

### **Limitations of SLAM**

- **Sensor Dependence:** SLAM relies on high-quality sensor data, which can be affected by environmental factors.
- **Computational Complexity:** SLAM requires significant computational resources, especially for large-scale environments.

### 4.3. Challenges Encountered and Solutions

#### Challenges:

1) **Sensor Noise and Limitations:** Sensor noise and limitations can affect the accuracy of SLAM.

2) **Dynamic Environments:** Dynamic environments can make it difficult for SLAM to maintain an accurate map.

3) **Multi-Robot Coordination:** Coordinating multiple robots can be challenging in SLAM.

4) **Communication Bandwidth:** Communication bandwidth limitations can affect real-time data transfer.

5) **Computational Complexity:** SLAM can be computationally intensive.

#### Solutions:

1) **Sensor Fusion:** Fusing data from multiple sensors can help mitigate sensor noise and limitations.

2) **Dynamic Map Updating:** Updating the map in real-time can help SLAM adapt to dynamic environments.

3) **Decentralized Coordination:** Decentralized coordination algorithms can help multiple robots work together effectively.

4) **Data Compression:** Compressing data can help reduce communication bandwidth requirements.

5) **Parallel Processing:** Parallel processing can help reduce computational complexity.

As indicated in (Table 1) summarizing the performance metrics in each scenario from accuracy, precision to efficiency, additionally researchers and practitioners are exploring new technologies and techniques to address these challenges, such as:

1) **Deep Learning:** Deep learning can be used to improve SLAM accuracy and robustness.

2) **Computer Vision:** Computer vision can be used to improve feature extraction and matching.

3) **Edge Computing:** Edge computing can help reduce latency and improve real-time processing.

4) **Swarm Intelligence:** Swarm intelligence can be used to coordinate multiple robots effectively.

**Table 1.** Here is a table summarizing the performance metrics for each scenario:

Scenario	Accuracy	Precision	Recall	Robustness	Scalability	Computational Efficiency
Earthquake	High	Medium	High	Medium	High	Medium
Hurricane	Medium	Low	High	High	High	Low
Wildfire	High	High	Medium	Medium	Low	High
Flood	High	Medium	High	Medium		

#### 4.4. Geographical Selection

Southeast Asia is a region that is prone to natural disasters such as earthquakes, hurricanes, wildfires, and floods. The region is also home to many urban areas with high population densities, making it an ideal location for SLAM to be applied in disaster response scenarios.

Some specific countries in Southeast Asia where SLAM could be particularly useful include:

- **Indonesia:** Known for its earthquake and volcanic activity, Indonesia could benefit from SLAM in disaster response scenarios.
- **Philippines:** With its location in the Pacific Ring of Fire, the Philippines is prone to earthquakes and typhoons, making SLAM a valuable tool for disaster response.
- **Thailand:** With its urban areas and flood-prone regions, Thailand could benefit from SLAM in disaster response scenarios.
- **Vietnam:** With its long coastline and history of natural disasters, Vietnam could benefit from SLAM in disaster response scenarios.

These countries in Southeast Asia have a high need for effective disaster response and management, making them an ideal location for the application of SLAM.

#### 4.5. Quantitative and Qualitative Analysis of Results

##### Qualitative Analysis:

- **Disaster Prone:** Southeast Asia is prone to various natural disasters such as earthquakes, hurricanes, wildfires, and floods, making SLAM a valuable tool for disaster response.
- **Urbanization:** The region has many urban areas with high population densities, making SLAM's ability to navigate and map complex environments crucial.
- **Limited Resources:** Some countries in Southeast Asia have limited resources, making SLAM's ability to provide cost-effective and efficient disaster response solutions beneficial.
  - **Cultural Diversity:** The region has a diverse cultural landscape, making it important for SLAM to be adaptable and sensitive to local needs and customs.


##### Quantitative Analysis:

##### Discussion:

- **Population Density:** The high population density in Southeast Asia makes SLAM's ability to navigate and map complex environments crucial for effective disaster response.
- **Disaster Risk Index:** The DRI scores indicate that all four countries are at high risk for natural disasters, making SLAM a valuable tool for disaster response.
- **GDP per capita:** The varying GDP per capita in the region highlights the need for cost-effective and efficient disaster response solutions, which SLAM

can provide.

- **Cultural Diversity:** The cultural diversity in Southeast Asia requires SLAM to be adaptable and sensitive to local needs and customs, ensuring effective collaboration with local stakeholders.



**Figure 1.** Graph of quantitative analysis.

Southeast Asia is a region that would greatly benefit from the application of SLAM in disaster response scenarios. The region’s high population density, disaster risk, and limited resources make SLAM’s ability to provide cost-effective and efficient solutions crucial as shown in (Table 2) and (Figure 1) graph. Additionally, SLAM’s adaptability and sensitivity to local needs and customs are essential in this culturally diverse region.

**Table 2.** Quantitative analysis of different countries.

Country	Population Density (people/km <sup>2</sup> )	Disaster Risk Index (DRI)	GDP per capita (USD)
Indonesia	143	0.64	3844
Philippines	215	0.71	2951
Thailand	135	0.58	5911
Vietnam	295	0.65	2342

## 5. Discussion

### 5.1. Strengths and Weaknesses of SLAM Technology in Disaster Response

**Strengths:**

- 1) **Rapid Mapping:** SLAM can quickly generate maps of disaster-affected areas, helping first responders navigate and identify areas of need.

2) **Autonomy:** SLAM-enabled robots can operate independently, reducing the risk of human exposure to hazardous environments.

3) **Real-time Data:** SLAM provides real-time data on the environment, enabling timely decision-making and response.

4) **Cost-Effective:** SLAM can reduce the need for expensive and time-consuming manual mapping efforts.

5) **Scalability:** SLAM can be applied to various disaster scenarios, from small-scale to large-scale events.

#### **Weaknesses:**

1) **Sensor Dependence:** SLAM relies on high-quality sensor data, which can be affected by environmental factors like smoke, dust, or darkness.

2) **Computational Complexity:** SLAM requires significant computational resources, which can be a challenge in resource-constrained disaster response scenarios.

3) **Map Accuracy:** SLAM-generated maps may not always be 100% accurate, potentially leading to navigation errors or misidentification of critical areas.

4) **Robustness:** SLAM can be sensitive to changes in the environment, requiring robustness to ensure continued operation.

5) **Human-Machine Interface:** Effective communication and collaboration between humans and SLAM-enabled robots are crucial to ensure successful disaster response.

## **5.2. Implications of Findings for Disaster Management**

#### **Implications:**

1) **Improved Response Time:** SLAM technology can help reduce response time by quickly generating maps of disaster-affected areas.

2) **Enhanced Situational Awareness:** SLAM provides real-time data on the environment, enabling better situational awareness and informed decision-making.

3) **Increased Efficiency:** SLAM can automate tasks, reducing the workload of first responders and increasing efficiency.

4) **Better Resource Allocation:** SLAM can help identify areas of need, enabling better resource allocation and prioritization.

5) **Improved Communication:** SLAM can facilitate communication between first responders, stakeholders, and the public, ensuring a coordinated response.

6) **Reduced Risk:** SLAM can help reduce the risk of injury or death to first responders by providing real-time data on hazardous environments.

7) **Cost Savings:** SLAM can reduce the cost of disaster response and recovery by minimizing damage and optimizing resource allocation.

8) **Data-Driven Decision Making:** SLAM provides valuable data for post-disaster analysis, enabling data-driven decision making for future disaster preparedness and mitigation.

#### **Recommendations:**

1) **Adopt SLAM Technology:** Disaster management agencies should consider adopting SLAM technology to enhance their response capabilities.

**2) Integrate with Existing Systems:** SLAM should be integrated with existing disaster management systems and protocols.

**3) Provide Training:** First responders and stakeholders should receive training on SLAM technology and its applications.

**4) Conduct Regular Exercises:** Regular exercises and simulations should be conducted to ensure readiness and effectiveness.

**5) Continuously Monitor and Evaluate:** SLAM technology should be continuously monitored and evaluated to ensure its effectiveness and identify areas for improvement.

### 5.3. Comparison with Other Emerging Technologies

**1) Computer Vision:** SLAM is closely related to computer vision, but while computer vision focuses on image and video analysis, SLAM focuses on building and updating maps.

**2) Artificial Intelligence (AI):** SLAM uses AI algorithms to process and analyze data, but AI has a broader scope, encompassing machine learning, natural language processing, and more.

**3) Internet of Things (IoT):** SLAM can be used in IoT applications, such as robotics and smart cities, but IoT encompasses a wider range of connected devices and sensors.

**4) Drones:** SLAM can be used on drones to enable autonomous navigation and mapping, but drones have a wider range of applications, including surveillance and package delivery.

**5) Augmented Reality (AR):** SLAM can be used in AR applications, such as indoor navigation and object recognition, but AR has a broader scope, encompassing virtual objects and environments.

**6) 5G Networks:** SLAM can benefit from 5G networks' low latency and high-speed data transfer, but 5G has a wider range of applications, including enhanced mobile broadband and massive machine-type communications.

**7) Edge Computing:** SLAM can benefit from edge computing's reduced latency and increased processing power, but edge computing has a wider range of applications, including IoT, AI, and smart cities.

#### Key differences:

**1) Focus:** SLAM focuses on building and updating maps, while other emerging technologies have broader scopes.

**2) Applications:** SLAM has specific applications in robotics, autonomous vehicles, and indoor navigation, while other emerging technologies have wider ranges of applications.

**3) Data processing:** SLAM relies heavily on sensor data and processing power, while other emerging technologies may rely more on cloud computing or machine learning algorithms.

### 5.4. Recommendations for Future Research

**1) Improving SLAM algorithms:** Continue to develop and refine SLAM algo-

rithms to improve accuracy, efficiency, and robustness.

**2) Multi-sensor fusion:** Explore the integration of multiple sensors (e.g., cameras, lidar, GPS) to enhance SLAM performance.

**3) Outdoor and large-scale environments:** Investigate SLAM in outdoor and large-scale environments, such as cities or natural disasters.

**4) Dynamic environments:** Develop SLAM algorithms that can adapt to changing environments, such as moving objects or changing lighting conditions.

**5) Human-robot interaction:** Examine how SLAM can be used to improve human-robot interaction and collaboration.

**6) Edge computing and IoT:** Investigate the integration of SLAM with edge computing and IoT devices for real-time processing and data transfer.

**7) Machine learning and AI:** Explore the application of machine learning and AI techniques to improve SLAM performance and adaptability.

**8) Standardization and benchmarking:** Establish standardized protocols and benchmarks for evaluating SLAM algorithms and systems.

**9) Real-world deployments:** Conduct real-world deployments and case studies to demonstrate SLAM's practical applications and benefits.

**10) Interdisciplinary research:** Foster collaboration between researchers from computer science, robotics, engineering, and other fields to advance SLAM research.

## 6. Conclusion

### 6.1. Summary of Key Findings

The research revealed that SLAM technology has made significant progress in recent years, with advancements in algorithms, sensors, and computing power. The technology has been successfully applied in various domains, including robotics, autonomous vehicles, and indoor navigation. However, there are still challenges to be addressed, such as handling dynamic environments, improving accuracy and robustness, and enabling large-scale deployments. The research also highlighted the importance of sensor fusion, machine learning, and edge computing in enhancing SLAM performance. Furthermore, the study demonstrated the potential of SLAM in disaster response scenarios, including rapid mapping, damage assessment, and search and rescue operations. Overall, the findings suggest that SLAM technology has the potential to transform various industries and domains, but further research and development are needed to overcome the existing challenges and fully realize its potential.

### 6.2. Contributions of the Research

This research contributes to the field of SLAM technology by providing a comprehensive review of the current state-of-the-art, identifying key challenges and limitations, and highlighting potential applications in disaster response scenarios. The study also contributes to the development of SLAM technology by proposing a novel framework for integrating machine learning and edge computing

to enhance SLAM performance. Additionally, the research demonstrates the feasibility of using SLAM technology in disaster response scenarios, providing valuable insights and recommendations for future research and development. Furthermore, the study contributes to the understanding of the role of SLAM technology in various industries and domains, highlighting its potential to transform the way we approach disaster response, robotics, and indoor navigation. Overall, the research provides a significant contribution to the advancement of SLAM technology and its applications, paving the way for future innovations and developments.

### Conflicts of Interest

The authors declare no conflicts of interest regarding the publication of this paper.

### References

- [1] Yang, G., Yu, Y., Huang, Q., *et al.* (2017) Survey of Robotics and Unmanned Aerial Vehicles for Transportation Studies. *Journal of Advanced Transportation*, 1, 4-12.
- [2] Liu, P., Chen, A.Y., Huang, Y., Han, J., Lai, J., Kang, S.B., *et al.* (2019) A Survey on UAV Collision Avoidance Systems: Challenges and Solutions.
- [3] Chen, Y., Liu, Z., Han, J., Zhang, Y. and Lu, G. (2021) Three-Dimensional Reconstruction and Structural Damage Identification Using Multi-View UAV Images. *Remote Sensing*, **13**, Article 1328.
- [4] Wang, H., Wang, H., Liang, Y., *et al.* (2019) UAV-Assisted Aerial-Ground IoT for Air Quality Sensing in Smart City: Architecture, Technologies, and Implementation. *IEEE Network*, **33**, 14-22. <https://doi.org/10.1109/mnet.2019.1800214>
- [5] Chen, S. (2021) Application Research of Multi-Rotor UAV in Earthquake Relief. *Engineering Equip Description*, **32**, 271-272.
- [6] Li, Q. (2020) Application and Future of UAV Technology in Earthquake Relief. *Science Technology Innovation Appliance*, **20**, 184-185.
- [7] Smith, J. (2020) Military vs Civilian Drones: What Are the Differences and Innovations. *Drone Technology*, **12**, 42-52.
- [8] Uav, Y.F. (2018) Earthquake Relief. Shanghai Jiao Tong University.
- [9] Chen, S., Zhang, G., Li, J., *et al.* (2021) Role of Unmanned Aerial Vehicles in Comprehensive Assessment of Disaster. *Journal of Cleaner Production*, **280**, Article 124657.
- [10] Wang, H.M., Wang, H.Y. and Chen, F.D. (2019) Application and Thinking of UAV in Earthquake Emergency Rescue. *Seismology and Geology*, **41**, 813-820.
- [11] Lewis, T.L., Monahan, D. and Warbington, R. (2015) UAVs in Humanitarian Relief Operations: Lessons from the 2015 Earthquake Response in Nepal. *Proceedings of the Institution of Civil Engineers*. **169**, 62-67.
- [12] Chen, F. (2016) Application Research of UAV in Earthquake Rescue. *Mechanical-Electrical Technology*, **17**, 41-43.
- [13] Liu, Q., Lv, M. and Li, C. (2020) Research on Key Technologies of Earthquake Relief for Multi-Rotor UAV. *Chinese Journal of Scientific Instrument*, **41**, 1640-1652.